SLOT IN PCS

# VPCF5-S55-G1-2A

## Key **Features**



- Light OS UEFI Shell allows scripting, file manipulation, and obtaining system information
- Ideal integrated solution for ViewBoard® interactive displays and presentation displays
- Powerful Intel® 12th Gen Core processors with embedded TPM 2.0
- DP1.4 port supports up to 5K resolution at 60Hz, delivering incredibly clear and detailed content
- Improved system stability, security, and thermal control

## Product **Description**

Seize the power to get more done by syncing your ViewBoard® Interactive Displays and Presentation Displays with the ViewSonic VPCF5-S55-G1-2A slot-in PC. Experience exceptional performance with Intel® 12th generation processors, 16GB DDR4 memory, and 512GB SSD storage, allowing you to breeze through any task at hand. Enhance productivity with dual-band WiFi, Bluetooth 5.2, and a range of ports, including 4K HDMI, 5K DP, USB 3.1, and Gigabit LAN RJ45 for faster workflows.

**Visit Us** www.viewsonic.com

## SOFTWARE

| | |
|---|---|
| Operating System: | UEFI Shel |

## CORE

| | |
|---|---|
| CPU: | Intel Gen12th core i5 CPU or later Gen. CPU |
| Graphics: | Intel Iris Xe Graphics (DP Supports up to 8K@30Hz, HDMI Supports up to 3840x2160@30Hz) |

## MEMORY

| | |
|---|---|
| Type: | DDR4 |
| Capacity: | 16GB |

## STORAGE

| | |
|---|---|
| Dimension: | M.2 SSD |
| Capacity: | 512GB |
| Interface: | PCIE |

## INPUT

| | |
|---|---|
| MIC(Microphone): | MIC-In&Line-Out two in one connector |
| OPS Standard: | 80 PIN x1 (HDMI 2.0 4K@60Hz, DP 5K@60Hz, USB3.0 x1 + USB2.0 x2, DC 12-19V) |

## OUTPUT

| | |
|---|---|
| HDMI: | x1 (Max 3840x2160@30Hz) |
| Audio: | MIC-In&Line-Out two in one connector |

## LAN

| | |
|---|---|
| RJ45: | x1 (RJ45 10/100/1000M) |

## WIRELESS / BLUETOOTH

| | |
|---|---|
| Wireless / Bluetooth: | Intel® Wi-Fi 6 AX101 WIFI 6 802.11 ax + BT5.2 |

## USB

| | |
|---|---|
| Type A: | USB 3.1 x 2 / USB 2.0 x 2 |
| Type C: | USB 3.1 Gen2 x 1 (Data Only) |

## POWER

| | |
|---|---|
| Voltage: | DC 19 V/ 4.74A |
| Consumption: | Max 90 W |

## OPERATING CONDITIONS

| | |
|---|---|
| Temperature (° C): | 0℃ ~ 40℃(working) |
| Humidity: | 20% ~ 80% RH Non-Condensing(working) |

## DIMENSIONS (W X H X D)

| | |
|---|---|
| Physical (inch / mm): | 7.87 x 4.68 x 1.18 in / 200 x 119 x 30 mm |
| Packaging (inch / mm): | 10 x 7.72 x 2.76 in / 254 x 196 x 70 mm |

## WEIGHT

| | |
|---|---|
| Net (lb / kg): | 1.54 lb / 0.7 kg |
| Gross (lb / kg): | 1.54 lb / 3.4 kg |

## PACKAGE CONTENTS

| | |
|---|---|
| PACKAGE CONTENTS: | 1. Quick Start Guide(With Compliance Statement )<br>2. Screws x 2<br>3. Antenna x 2 |

Copyright © ViewSonic Corporation 2000-2024. All rights reserved.